

Technical data

DA20262702 - RM075P-3615-260

| Parameter | Value | Unit |
|---------------------------|-------|-----------|
| Rated Force | 460 | N |
| Rated Current | 9 | Arms |
| Peak Force | 1058 | N |
| Peak Current | 21 | A |
| Force Constant | 51,8 | N/A |
| BEMF Constant | 29,9 | V/m/sec |
| Phase to phase Resistance | 3,27 | ohm |
| Phase to phase Inductance | 26 | mH |
| Pole Pitch | 32 | mm |
| Max stroke | 260 | mm |
| Max power dissipation | 426.4 | W |
| Thermal resistance | 0.184 | degrees/W |

DA20260303 - RM075P-2415-120

| Parameter | Value | Unit |
|---------------------------|-------|-----------|
| Rated Force | 460 | N |
| Rated Current | 6,2 | Arms |
| Peak Force | 1058 | N |
| Peak Current | 14,3 | A |
| Force Constant | 74,1 | N/A |
| BEMF Constant | 42,8 | V/m/sec |
| Phase to phase Resistance | 4,9 | ohm |
| Phase to phase Inductance | 39 | mH |
| Pole Pitch | 32 | mm |
| Max Stroke | 120 | mm |
| Max power dissipation | 378.9 | W |
| Thermal resistance | 0.276 | degrees/W |

From:

<https://www.nilab.at/dokuwiki/> - **NI-LAB GmbH**
Knowledgebase

Permanent link:

https://www.nilab.at/dokuwiki/doku.php?id=rm_linear:technical_data

Last update: **2026/06/02 06:11**

